

XDS-1078-A9

Advanced 10.1" Interactive Room Panel

Industry's First Android 9.0 Meeting Room Panel —
Highly Responsive & Secure



Android 9
By Google

Latest OS from Google.
Continuous security
updates for reliability



PoE+ / PoE

Minimalist installation
keeps workplaces
simple & modern



2.8 cm Slim
Design

Built in zero gap
flush for secure,
versatile mounting




High Visibility
Status Light

Elegant light bars with
soft illumination that is
easy on the eyes



Orientation Aware

Easy to integrate into
workplace design
in portrait and landscape



High Performance
Processor

Powers smooth,
responsive, and vibrant
user experience



10-Point
Multi-Touch

Quick check in/out or book room
at the door. Zoom and scroll for
easy browsing



Remote Device
Management

Easily manage, monitor &
troubleshoot all
in-service room panels

Technical Specifications

Display

- 10.1" LCD panel
- 10 points capacitive multi-touch
- 300 nits maximum brightness
- 1280 x 800 panel resolution
- Viewing angle (H/V): 170 / 170
- 6 Primary colors LED side bar x 2

Internal Player

- Processor: Cortex-A53 Octa-core
- System memory: 2.0 GB
- Flash memory: 16 GB eMMC built-in

Connectivity

- Wi-Fi: 802.11 b/g/n
- Micro USB for ADB
- Ethernet RJ45: 10/100BASE-T
- USB 2.0 x 2
- Built-in 1W stereo speaker x 2
- 3.5 mm analog stereo audio out
- Optional 3G / 4G mobile module via USB
- Micro SD card slot, memory expandable to 16 GB / 32 GB / 64 GB (card replaces internal storage)

Room Management Software

- ResourceXpress room screen licence required

Advanced Features

- ResourceXpress remote device management
- Device health/connectivity monitoring
- Central management of location based settings
- MAC Address validation security
- Touchless interactive operation
- Equipment fault reporting

Supplied Accessories

- HW QSG
- Built in VESA compatible 75 mm x 75 mm posts
- Back cover screws x 2 pcs
- Flush mount back cover

Optional Accessories

- Power adapter
- Expansion port connector
- Premium Wall Mount

Power Requirement

- Input: 100 - 200 V, 50 - 60 Hz
- Output: 12 V, 1.5 A
- UL / CB certified power supplies
- Interchangeable connector system includes
- US plug (optional for EU, UK, and AUS plugs)
- IEEE 802.3 at Power-over-Ethernet (PoE+)

Environmental

- Operating temperature: 0 to 40 °C
- Humidity: 10 to 85 % @ 40 °C non-condensing

Dimensions for Product & Package

- System Dimension: 270 mm x 171 mm x 28.5 mm (10.62" x 6.72" x 1.12")
- System Weight: 727g
- Individual package size: 336 mm x 100 mm x 227 mm
- Outer carton size: 523mm (W) x 356mm (D) x 259mm (H)
- Units per outer carton: 5 pcs

Certifications

- CE / FCC/RoHS

Warranty

- 1 year limited parts & labor (optional three years advance replacement available with ResourceXpress Warranty Plus)



USA

ResourceXpress Inc, 467 Forrest Ave, Unit 119, Cocoa, FL 32922

Tel: +1-201 256 1601
Email: ussales@qedas.com

www.ResourceXpress.com

UK

QED ResourceXpress, 22 Bridgwater Court, Weston-super-Mare, BS24 9AY

Tel: +44 (0)1934 836960
Email: sales@qedas.com